

# FULGOR

## MILANO

### 700 Series 30" Self Cleaning Single Wall Oven

**F7SP30S1**



<b>Series</b>	<b>700</b>
Type	PYRO
Size	30"x30"
Colour	<b>SS</b>
Stainless Steel Aesthetics	Embossed window profile with bended edges
Oven Type	Multifunction 2 Fans (True Euro Convection)
Temperature Regulation	Full Electronic

Key	Functions		
LIGHT	LIGHT		•
DEHIDR	DEFROST		•
	DEHYDRATE		•
KEEP WARM	WARM		•
	WARM +		•
BAKE	BAKE		•
	ROAST		•
	TRUE CONVECTION BAKE		•
CONV.	CONVECTION ROAST		•
	CONVECTION BAKE		•
	CONVECTION GRILL		•
PIZZA	CONVECTION BROIL		•
	PIZZA		•
BROIL	BROIL LEVELS		•
SELF C.	SELF CLEAN		•

<b>Control Panel</b>	
Control type	MODULAR - Electronic
Display	TFT 3,5"
Menu Recipes	•
Commands	Full Touch
Language	11

<b>Special Features</b>	
Demo Mode	•
Brightness setting (ON condition)	•
Brightness setting (OFF condition)	•
Beeper volume setting	•
Date format	•
Automatic Fast Preheat	•
Classic PIZZA function 310°C	•
Child Door Lock	•

# FULGOR

## MILANO

Commands Lock	•
Sabbath mode	•
12/24 hours clock format	•
°C/°F degree unit	•
Door miscro switch	•
Event logs (for Service)	•
<b>Oven Door(s)</b>	
Oven Glass Window	Large See Through Glass
Door Cooling System	4 Pane Heat Resistant Glass
Door Hinges	Heavy Duty Steady Tilt
<b>Oven Cavity</b>	
Gross Capacity (cbft)	4.4
Net Capacity (cbft)	4.1
Cavity Enameling Colour	Black
Rack Positions	6
Oven Lights	3 or 2 x 20W Halogen
Broil Upper Heating Element	3500 W (240V)
Upper Auxiliary Element Wattage	1032W (240V)
Concealed Bake Lower Heating Element	3000 W (240V)
Convection Element Wattage	2x1300W (240V)
<b>Oven Accessories</b>	
Chromed racks	•
Enameled Grill set ( basin + anti splash )	•
Telescopic chromed rack	•
Meat probe	•
<b>Dimensions/Weight - (In or Lbs)</b>	
Overall dim - width	29 11/16" (754mm)
Overall dim - height	27-7/8" (707mm)
Overall dim - depth	24" (610mm)
Cutout - width	28 7/16" (722mm)
Cutout - height (min)	27-1/4" (692mm)
Cutout - depth (min)	23-1/4" (590mm)
<b>Power / Ratings (208/240 V, 60 Hz)</b>	
KW/Amps rating at 240V, 60Hz	3.70kW - 15.4A
KW/Amps rating at 208V, 60Hz	3.50kW - 16.8A
Cable + Conduit	•
<b>INSTRUCTIONS FOR USE</b>	
Use & Care Manual	EN, SP, FR
Installation Manual	EN, SP, FR